



Three Point Linkage Rollermower

The 6000, 6300, 8000 & 8400 Groundsmajor Rollermowers easily connect to the tractors three point linkage and roll over the ground following the earth's contours independently of the tractor.

The blade system is enclosed within an aerofoil chamber and cut material is recycled and distributed evenly in the wake of the machine. The finish is a professional stripe which is favoured by grounds maintenance keepers.

A simple spanner adjustment sets and locks the cutting height of the machine by raising or lowering the rollers. The cutting range available is from 12mm to 150mm.

Heavy duty rollers are fitted with internal bearings and seals to prevent water and dust contamination ensuring life long protection. The MAJOR Groundsmajor Rollermower range are all gear driven machines which results in low maintenance & down time costs when compared to belt driven machines.

The gear drive system allows these machines to operate in the most arduous weather conditions and still produce a perfect finish.

The slip clutch and overrun protection on the input PTO shaft coupled with the rubber buffer protection between each of the rotor gearboxes minimize damage to vital components in the event of an impact.

This machine is suitable for use in a wide range of applications including cricket outfields, sports pitches, polo grounds, school grounds and golf course rough maintenance.

Standard Features:

- Mulching chambers to ensure even distribution of material
- Adjustable working depth from 12mm to 150mm
- 3 point linkage Cat I/II Arms
- Inter gearbox shock loading protection
- Slip clutch and overrun on PTO shaft
- Machined roller bearing housings
- Choice of twin cut blades on the 6000 and 8000 models
- Choice of fixed or swinging blades on 6300 and 8400 models
- Heavy duty rollers
- Durable two pack paint finish

Model	Working Width	Power (HP)	Weight	PTO RPM	No. of Rotors	No. of Blades	Cutting Height
6000	1.8m	25-50	475 kg	540	2	8	12-100mm
6300	1.95m	25-50	450 kg	540	3	3	12-150mm
8000	2.4m	30-60	650 kg	540	2	8	12-100mm
8400	2.4m	30-60	510 kg	540	4	4	12-150mm