

Agri Slurry Tanker

Farmer Specification

These tankers are available in capacities from 1500 to 2000 gallons. There is a detachable parking stand and PTO holder fitted as standard. All MAJOR tankers are constructed from 6mm steel for maximum strength. The axle is a heavy duty agricultural spec axle.

To comply with applicable legislation, the 1700 agri model is fitted with a safety breakaway cable.

The LGP models have hydraulic brakes as standard ensuring compliance with the regulations for this model of tanker.

Rubber buffers are fitted as standard on the drawbar to give a smoother and safer journey. These tankers are galvanised as standard.





Tyre	550/60/22.5	21.3 R24
W (mm)	550	540
D (mm)	1170	1400
1700 Std	•	•








Tyre	28.1 R26 Nortec	800/65/R32 Nortec 181
W (mm)	740	798
D (mm)	1780	1820
1500 LGP	•	•
1700 LGP	•	•
2000 LGP	•	•



The joints on the tank are welded to ensure a high-quality and visually perfect weld seam.





Hydraulic brakes as standard ensuring compliance with the regulations for this model of tanker



Drawbar is fitted with rubber buffers to give a smoother and safer journey







Fitted with safety breakaway cable for safer use on public highways.



Detachable parking stand and PTO holder

Model	Tyre options	Capacity		OA Length	OA Width	OA Height	Wheel	Weight (Kg)	
		Gallon	Litres	(Hitch to coupling ball)	(Depends on tyre)		Empty	Full	
1700 Agri	550/60/22.5	- 1,685	7,660	6.4m	2.6m	2.9m	No	2,550	10,210
	21.3 R24								
1500 LGP Ag	28.1 R26 Nortec	1,485	6,750	6.0m	2.6m	3.0m	YES	2,994	9,744
	800/65/R32 Nortec 181	1,420	6,455	6.0m	2.6m	3.0m	YES	3,150	9,605
1700 LGP Ag	28.1 R26 Nortec	1,610	7,319	6.4m	2.6m	3.0m	YES	3,330	10,649
	800/65/R32 Nortec 181								
2000 LGP Ag	28.1 R26 Nortec	- 2,040	9,271	6.6m	2.6m	3.2m	YES	7.540	12,811
	800/65/R32 Nortec 181							3,540	







17

16 www.major-equipment.com www.major-equipment.com