

Disc Injector

Slurry Application Unit

The MAJOR 5.2m Disc Injector is a combined soil fertilising and furrowing machine with a working depth from 20mm (3/4") to 60mm (21/2"). A powerful Vogelsang macerator delivers slurry evenly through 40mm pipes. The slurry is inserted into slits created by the spring steel self sharpening cutting discs. The unit folds hydraulically giving a 2.4m transport width.

The MAJOR Disc Injector operates best in grass/stubble of a height between 60-100mm (21/4-4"). When working, the spring loaded discs create slits of 20-60mm deep which are completely filled with slurry.

The slurry is only visible as narrow strips between the grass. The distance between the slits is 200mm (8").

Model	MJDI-5200
Working Width	5.2m (16′ 5″)
Transport Width	2.4m
No. of Outlets	26
Working Depth	20-60mm
Weight	1380kg
Spread Capacity	10 - 30 m3 / ha



Features

- √ 300mm self sharpening solid cutting discs spaced at 200mm (8") intervals
- ✓ Automatic mechanical shoe shut off to prevent spillage
- Mechanical suspension on individual discs
 Individual disc steerage
- ✓ Depth regulated by hydraulic linkage.
 (Hydraulic requirement: 50 70 litre/min @ 230 bar max)