



Flex Wing Topper

Three Point Linkage

The MAJOR Flex Wing Topper is a three point linkage mounted machine which folds up to 2.3m (7' 6") transport width.

Like all MAJOR machines, the Flex Wing Topper is of robust construction. CE conformity is achieved through full PTO guarding and heavy rubber skirting to prevent debris from escaping.

The wing cutting decks are raised by hydraulic control to transport position.

The wings are capable of flexing from -15 to +25 degrees allowing the cutting unit to follow the ground contours.

Features

- ✓ Galvanised finish
- ✓ Robust pivot points
- ✓ Rubber shock absorbers
- ✓ Shearbolt PTO protection
- ✓ Hydraulic wing lift
- ✓ ProCut swinging blades
- ✓ 88mm (3 1/2") blade overlap to eliminate striping

Contra-rotating swinging blades are retained in hardened steel bushings and clamped by sprung steel blade backs.

Under-sole discs are fitted to prevent scalping and ensure a perfect finish every time.

	MJ38-540
Overall width	5.60m (18' 4")
Working width	5.40m (18')
Transport width	2.3m (7' 6")
Rotors	6
Blades	12
Power	80-120 HP
PTO rpm	1000
Blade speed	74m/s
Cutting height	50-250 mm
Weight	1395 kg