



Swift Roller Mower

Trailed

Offering the same qualities found in the three-point linkage models, the Swift trailed winged roller mower is designed to meet – and exceed – the requirements to maintain vast areas of grass for contractors, turf farms and local authorities.

Unlike other machines on the market, these wide area mowers are fitted with brakes and an LED lighting kit as standard to ensure safe transport between sites.

High-performance Strenx™ 700 MC structural steel makes these roller mowers strong. Combined with hot-dip galvanisation to EN ISO 1461:2009 specifications, these roller mowers outlive most of its competitors and retain their values.



Features

- ✓ Simple height adjustment from 10-130mm for versatile and year round mowing
- ✓ Gear-driven power line for low maintenance
- ✓ Walterscheid wide-angle PTO shafts
- ✓ Sealed internal roller bearings for total protection against moisture, soil and debris
- ✓ LED road lighting kit and fully braked for safe and legal road work
- ✓ 3-year MAJOR warranty

Option for Racecourses

- ✓ Standard roller fitted to the rear and a modified roller to the front
- ✓ Castor wheels (1 per wing) to the front for superior cutting in a variety of grass heights.

The MAJOR Swift has a direct drive with gearboxes on each blade which copes with short grass and longer grass as well. We cut all that with one mower instead of buying a whole fleet, reducing our purchasing costs. MAJOR mowers are cheap to run, cheap to maintain, but have that build and quality that will give you the perfect finish.

**WILL POWER, AREA MANAGER,
CARDIFF COUNCIL PARKS SERVICES**



Option of a castor wheel per wing for racecourse applications



Two in one blade system, rigid and swinging



10-130mm height adjustment for year round mowing

Model	MJ71-400T	MJ71-540T	MJ71-600T	MJ71-730T
Overall Width	4.16m (13' 8")	5.54m (18' 2")	6.21m (20' 5")	7.42m (24' 5")
Working Width	4.00m (13' 1")	5.40m (17' 9")	6.00m (20')	7.30m (24')
Transport Width	2.40m (8')	2.40m (8')	2.60m (8' 6")	2.60m (8' 6")
Power (HP)	60-110 HP	70-120 HP	90-130 HP	105 - 150 HP
PTO rpm	540	540	1000	1000
Cutting Height	10-130mm	10-130mm	10-130mm	10-130mm
Rotors	6	8	9	11
Blades	12	16	18	22
Weight	1665kg	1830kg	2025kg	2270kg
Blade tip speed	75 m/s	75 m/s	70 m/s	70 m/s
Mowing Rates (Acres/hr at 7mph)	11.4	14.9	16.8	20.4