



MJ24 Flail

Scan the QR code to see a working video



The MAJOR MJ24 Flail Mower is a robust machine designed for heavy grass cutting. The machine is offset by hydraulic control as standard.

This machine suitable for pruning in the harshest of working conditions such as vineyards, orchards and green areas.

- ✓ Three point linkage CAT II
- ✓ Hydraulic side shift
- ✓ Rear roller and side skids
- ✓ Adjustable rear cover
- ✓ Rotor with hammers

Product specifications		
Model	MJ24-230	MJ24-280
Working Width	2.3m (7' 6")	2.74m (8' 11")
Overall Width	2.6m (8' 6")	3m (9' 10")
Machine Height	1.1m	1.1m
Machine Depth	1.2m	1.2m
Hammers	26	30
Power (HP)	from 80HP	from 100HP
PTO rpm	540	540
Belts	4	5
Weight	794kg	916kg
Mounting Position	Rear	Rear

MJ26 Flail

The MAJOR MJ26 flail can be fitted to any tractor front or rear Cat II linkage, independently of the PTO direction.

This machine is suitable for the clearance of small trees, bush and heavy grass in amenity areas and on the verges of highways. It is also suitable for trimming grass and lighter growth as the blades can be easily changed.

- ✓ Double 3 point linkage (front/rear) Cat II
- ✓ Hydraulic side shift
- ✓ PTO shaft c/w overrun
- ✓ Gearbox with double PTO
- ✓ Rear roller and side skids
- ✓ CE certified; PTO guarding and safety flaps



Product specifications		
Model	MJ26-230	MJ26-280
Working Width	2.3m (7' 6")	2.74m (8' 11")
Overall Width	2.6m (8' 6")	3m (9' 10")
Machine Height	1.1m	1.1m
Machine Depth	1.2m	1.2m
Hammers	26	30
Power (HP)	from 80HP	from 80HP
PTO rpm	540 - 1000	540 - 1000
Belts	4	5
Weight	900kg	1026kg
Mounting Position	Rear	Rear/Front