



Offset Topper

trailed

Scan the QR code to see a working video



The MAJOR Trailed Topper is a fully offset gear driven machine. It is offset for working and is folded into transport position hydraulically from the tractor seat.

The rotors are timed with each other and have an overlap of 3 inches (75mm). The blades rotate in opposite directions to each other and spread the cut grass evenly behind the machine. As the machine is fully offset there

is no trampling of the pasture prior to cutting. The cutting height is set at the desired level by moving the adjustable side skids to the appropriate position. There is a limit stop on the ram which controls the rear axle.

- ✓ Full hydraulic offset control
- ✓ Hydraulic breakaway system
- ✓ Wide angle PTO shaft
- ✓ Twin-cut ProCut swinging blades



Product specifications			
Model	8FTGD-HD	9TFGD-HD	12FTGDW-HD
Transport Width	2.6m (8' 5")	2.9m (9' 5")	2.6m (8' 5")
Working Width	2.4m (8')	2.7m (9')	3.57m (12')
No. of Rotors	2	2	3
No. of Blades	8	8	12
Power (HP)	35-100 HP	40-110 HP	40-120 HP
PTO rpm	540	540	540
Blade Speed	70m/s	77m/s	70m/s
Cutting Height	50-205 mm	50-205 mm	50-205 mm
Weight	550 kg	650 kg	1240 kg